







	Engine	Briggs & Stratton 16 Vanguard V-Twin OHV Start electric, with 12 V battery Supply fuel Displacement 479 cc, 2 Cylinders Power 14 HP (10.3 kW) - Gross power 16 HP Air cooled Dry air filter with interchangeable filter cartridges
	Fuel tank capacity	Fuel tank 7 litres (reserve tank 1 litre)
	Gearbox	hydrostatic transmission
	Clutch	Clutch: electromagnetic for PTO with blade brake
	Cutter deck	side discharge and mulching, with "QUICK SHIFT" lever in order to change the cutting function
	Cutting configuration	rotating single blade with floating terminals
	Cutting width	830 mm
	Cutting height	6 different cutting positions from 25 to 80mm plus 1 for transfer
	Peripheral blade speed	72 m/s
	Differential locking	Differential lock device by pedal action
	Front tyres	Turf 13x5.00-6
	Rear tyres	Turf 16x7.50-8
	Speed	continuously variable from 0 to 9 km/h, reverse gear from 0 to 6 km/h
	Inner turning radius	45 cm
	Seat	Dampened seat, adjustable, with armrests and roll bar
	Parking brake	rear parking disc brake
	Mowing capacity per hour (indicative)	6000 m ² /h
	Standard features	Tow bar and front headlight
	Length	1895 mm
	Width	1130 mm
	Height	1025 mm
	Weight	238 kg

 **In action! Photos and Videos**

[Back to](#)



The GRILLO MD16 cutter deck is equipped with a 'Quick Shift' lever which allows you to change from mulching cut mode to side discharge cut mode.